


	Question	Government Response
1	Set shoulder patch - no pattern on pattern list, Table IX page 18-19, please clarify.	The IWCS does not contain shoulder patches. As such; delete "and shoulder patches" from the purchase description (see p. 20, Table X).
2	Zipper thong - fabric or tape? Also, please provide measurements.	The slide fastener thong shall be constructed using basic material as specified in paragraph 3.3.2.1.1, stretch woven. The slide fastener thong shall finish 1-1/2" long. (see p. 16, para 3.4.2.3.1)
3	Pocket and pocket flap patterns not according with specifications. Please clarify the zipper location.	<p>The two sleeve pockets shall be constructed with a bottom bellow, sewn eyelet drainage hole located in the bottom bellow, and a concealed two-button closure flap (see p. 15, para 3.4.1).</p> <p>A slide fastener is not used in construction of the pockets. Pockets shall be constructed according to the provided patterns. Delete ", the pocket slide fastener shall finish 5-1/2 inches in length" (see p. 16, paragraph 3.4.2.3, line 2).</p> <p>Pocket closure buttons shall be as follows: The buttons shall be dull finish, 4-hole, 3ligne, and shall be in accordance with the following button style:</p>  <p>The color of the buttons shall be a good match to Coyote 498 (see p. 16, para 3.4.2.4).</p>
4	Drawings not according with the specifications. Example 1: set flap - not in table X but in figure 1 calls for SN. Example 2: The topstitch of the yoke on Table X is in SN and the figure 1 is DN. Please clarify.	The topstitching shall be as shown in Figures 1 and 2. In Table X, page 20, Yoke Seams, delete "LSbm-3" and substitute "LSbm-4" (see p. 20, Table X).
5	The location of the 2" x 2" loop the pattern show the X- box stitching and figure 1 the Velcro doesn't have the X-box stitching. Please clarify.	The loop fastener tape shall be attached as specified on the pattern piece; the attachment method shall include the Box-X stitching (see p. 16, para 3.4.2.3).
6	PD 3.4.2.3 Slide Fasteners. Lists the color for all	All types, to include the Navy and Woodland

	types as Coyote 498 would this also apply to the Navy and Woodland Patterns?	pattern, shall be constructed using the Coyote 498 slide fastener (see p. 16, para 3.4.2.3).
7	PD 3.4.3 Label. States the shirt shall have 3 permanent labels- I only see 2 listed. The 3rd label listed is the paper hang tag?	The IWCS is manufactured with two permanent labels, as such delete "three" and substitute "two" (see p. 16, para 3.4.3).